

Royal® Flushometer 186-1

▶ Code Number

3012636

Description

Exposed Urinal Flushometer, for 3/4" top spud urinals.

► Flush Cycle

Model 186-1.0 Low Consumption (1.0 gpf/3.8 Lpf)

▶ Specifications

Quiet, Exposed, Diaphragm Type, Chrome Plated Urinal Flushometer with the following features:

- PERMEX® Synthetic Rubber Diaphragm with Dual Filtered Fixed Bypass
- ADA Compliant Metal Oscillating Non-Hold-Open Handle with Triple Seal Handle Packing
- Spud Coupling and Flange for 3/4" Top Spud
- Sweat Solder Adapter with Cover Tube & Cast Wall Flange with Set Screw
- Non-Hold-Open Handle, Fixed Metering Bypass and No External Volume Adjustment to Ensure Water Conservation
- Flush Accuracy Controlled by CID Technology
- Diaphragm, Handle Packing and Vacuum Breaker to be molded from PERMEX® Rubber Compound for Chloramine Resistance


Accessories (Sold Separately)

See Accessories Section of the Sloan catalog for details on these and other Flushometer variations.

▶ Fixtures

Consult factory for matching Sloan brand fixture options.





► Compliance & Certifications









This space for Architect/Engineer Approval